



National Aeronautics and Space Administration
Langley Research Center
Hampton, Virginia 23681-2199

Cloud – Aerosol LIDAR and Infrared Pathfinder Satellite Observations (CALIPSO)

Data Description and Quality Summary

Wide Field Camera Level 1B Assembler Data

Cloud – Aerosol LIDAR and Infrared Pathfinder Satellite Observations

Data Description and Quality Summary
Wide Field Camera Level 1B Assembler Data

Primary Authors

Brian Getzewich, Michael Pitts, Charles Trepte, David Winker, Jason Tackett, Mark Vaughan
NASA Langley Research Center
Hampton, Virginia 23681-2199

Jacques Pelon
LATMOS/IPSL, Université Pierre et Marie Curie
75252 Paris Cedex 5 (France)

Anne Garnier, Jayanta Kar, Kam-Pui Lee
Analytical Mechanics Associates (AMA)
21 Enterprise Parkway, Hampton, Virginia 23666

Timothy Murray, Sharon Rodier
ADNET Systems, Inc.
6720B Rockledge Drive, Suite #504, Bethesda, Maryland 20817

Robert Ryan
Coherent Applications, Inc. – Psionic LLC
1100 Exploration Way, Hampton, Virginia 23666

January 21, 2026

CALIPSO WFC Level 1B Assembler Data Description Document

Version 4.00

Data Version: 4.00
Data Release Date: October 01, 2025
Data Date Range: June 13, 2006 to April 10, 2020

Introduction

The primary Wide Field Camera (WFC) Level 1B data products are calibrated radiance and bidirectional reflectance registered to an Earth-based grid centered on the Lidar ground track. During the normal operation, the WFC acquires science data only during the daylight portions of the CALIPSO orbits. For each orbit, three different data files are produced: 1 km Native Science grid, 125 m Native Science grid, and 1 km Registered Science grid. The 1 km Native Science grid covers the full 61 km swath centered on the Lidar track. The 125 m Native Science grid contains only the central 5 km wide high resolution portion of the WFC swath. The 1 km Registered Science grid provides WFC data on the identical grid as the CALIPSO IIR data and is produced to facilitate the use of the WFC data in the IIR retrievals. In addition to radiance and reflectance grids, the WFC Level 1 data products include two parameters that quantify the homogeneity of the cross track image frames: swath homogeneity and track homogeneity.

There are also two intermediate WFC Level 1B data products: Assembler and Calibration. The calibration data product contains geolocated nighttime digital count data. The calibration data is collected over a 25-second segment on the dark side of every orbit. The assembler data products contain geolocated nighttime daily digital count and daily statistical data which comes from the calibration product. The assembler algorithm takes the calibration data and calculates the statistics for each pixel (mean, standard deviation, maximum, and minimum).

This document will focus on the Assembler data product.

Table of Contents

| | |
|--|---|
| Introduction | 3 |
| Additional Documentation..... | 4 |
| Data Product Descriptions | 4 |
| 1Km_Row_Time | 4 |
| 1Km_Row_UTC_Time..... | 5 |
| 125m_Row_Time | 5 |
| 125m_Row_UTC_Time..... | 5 |
| 1Km_Latitude | 5 |
| 1Km_Longitude | 5 |
| 1Km_Pixel_Values | 5 |
| 125m_Pixel_Values | 6 |
| Col_Number_of_Center_Image_Pixel | 6 |
| Row_Number_of_Center_Image_Pixel | 6 |

| | |
|--|---|
| CCD_Temperature..... | 6 |
| BasePlate_Temperature | 6 |
| 1Km_Pixel_Values_Mean..... | 6 |
| 125m_Pixel_Values_Mean..... | 7 |
| 1Km_Pixel_Values_St_Dev..... | 7 |
| 125m_Pixel_Values_St_Dev..... | 7 |
| 1Km_Pixel_Values_Max..... | 7 |
| 125m_Pixel_Values_Max..... | 7 |
| 1Km_Pixel_Values_Min..... | 7 |
| 125m_Pixel_Values_Min..... | 7 |
| Metadata Parameter Descriptions..... | 8 |
| Product_ID | 8 |
| Date_Time_at_Granule_Start..... | 8 |
| Date_Time_at_Granule_End..... | 8 |
| Date_Time_of_Production..... | 8 |
| Frame_Time | 8 |
| Integration_Time..... | 8 |
| Relevant External Documentation | 8 |
| Data Release Information | 8 |
| Data Quality Information | 9 |
| Data Quality Statement for the release of the CALIPSO WFC Level 1 Product Version 4.00 | 9 |
| Data Quality Statement for the release of the CALIPSO WFC Level 1 Product Version 3.02 | 9 |
| Data Quality Statement for the release of the CALIPSO WFC Level 1 Product Version 3.01 | 9 |
| Data Quality Statement for the release of the CALIPSO WFC Level 1 Product Version 1.10 | 9 |

Additional Documentation

- CALIPSO Data Management Team: CALIPSO Data Products Catalog, PC-SCI-503, Release 5.00.
- CALIPSO Algorithm Theoretical Basis Document, Wide Field Camera (WFC) Level 1 Algorithms (PC-SCI-205), Release 1.0, 25 October, 2005.

Data Product Descriptions

1Km_Row_Time

Units: s

Format: Float_64

Valid Range: 4.203E8, 9.623E8

Description: Reports the International Atomic Time (TAI) in elapsed seconds from January 1, 1993 for the 1 km resolution.

1Km_Row_UTC_Time

Units: yymmdd.ffffff

Format: Float_64

Valid Range: 60428, 230701.0

Description: Reports the Coordinated Universal Time (UTC); format = yymmdd.ffffff, where yy is a two digit data acquisition year number (06 to 23), mm is a month number (01 to 12), dd is a day number (01 to 31), and fffffff is the elapsed fraction of the data acquisition day. This parameter is for the 1km resolution.

125m_Row_Time

Units: s

Format: Float_64

Valid Range: 4.203E8, 9.623E8

Description: Reports the International Atomic Time (TAI) in elapsed seconds from January 1, 1993 for the 125 m resolution.

125m_Row_UTC_Time

Units: yymmdd.ffffff

Format: Float_64

Valid Range: 60428, 230701.0

Description: Reports the Coordinated Universal Time (UTC); format = yymmdd.ffffff, where yy is a two digit data acquisition year number (06 to 23), mm is a month number (01 to 12), dd is a day number (01 to 31), and fffffff is the elapsed fraction of the data acquisition day. This parameter is for the 125 m resolution.

1Km_Latitude

Units: degrees_north

Format: Float_64

Valid Range: -90.0, 90.0

Description: Reports the latitude of the individual 1 km WFC pixel on the surface.

1Km_Longitude

Units: degrees_east

Format: Float_64

Valid Range: -180.0, 180.0

Description: Reports the longitude of the individual 1 km WFC pixel on the surface.

1Km_Pixel_Values

Units: count

Format: UInt_16

Valid Range: 0, 20000

Scale Factor: 1

Offset: 0

Description: Nighttime digital counts measured by WFC at 1 km resolution.

125m_Pixel_Values

Units: count

Format: UInt_16

Valid Range: 0, 20000

Scale Factor: 1

Offset: 0

Description: Nighttime digital counts measured by WFC at 125 m resolution.

Col_Number_of_Center_Image_Pixel

Units: No Units

Format: UInt_32

Valid Range: 244, 268

Description: The column number of the center image pixel.

Row_Number_of_Center_Image_Pixel

Units: No Units

Format: UInt_32

Valid Range: 229, 258

Description: The row number of the center image pixel.

CCD_Temperature

Units: degC

Format: Float_32

Typical Range: -100.0...100.0

Description: Temperature of the focal plane of the WFC Charge Coupled Device (CCD) array. The temperature of the WFC detector is actively controlled by a Thermoelectric Cooler (TEC). The set point is 0°C and the nominal range is about +/-0.5°. Larger excursions have been observed with no impact on the data quality. However, if excursions exceed more than about +/-5°, the data should be used with caution.

BasePlate_Temperature

Units: degC

Format: Float_32

Typical Range: -100.0...100.0

Description: Temperature of the feet of the WFC housing. Typically ranges between 10°C and 20°C. Primarily used as a diagnostic tool.

1Km_Pixel_Values_Mean

Units: count

Format: Float_32

Valid Range: 0.0, 20000.0

Description: The average of the nighttime digital counts measured by WFC at 1 km resolution for the current day for that pixel.

125m_Pixel_Values_Mean

Units: count

Format: Float_32

Valid Range: 0.0, 20000.0

Description: The average of the nighttime digital counts measured by WFC at 125 m resolution for the current day for that pixel.

1Km_Pixel_Values_St_Dev

Units: count

Format: Float_32

Valid Range: 0.0, 20000.0

Description: The standard deviation of the nighttime digital counts measured by WFC at 1 km resolution for the current day for that pixel.

125m_Pixel_Values_St_Dev

Units: count

Format: Float_32

Valid Range: 0.0, 20000.0

Description: The standard deviation of the nighttime digital counts measured by WFC at 125 m resolution for the current day for that pixel.

1Km_Pixel_Values_Max

Units: count

Format: Float_32

Valid Range: 0.0, 20000.0

Description: The maximum of the nighttime digital counts measured by WFC at 1 km resolution for the current day for that pixel.

125m_Pixel_Values_Max

Units: count

Format: Float_32

Valid Range: 0.0, 20000.0

Description: The maximum of the nighttime digital counts measured by WFC at 125 m resolution for the current day for that pixel.

1Km_Pixel_Values_Min

Units: count

Format: Float_32

Valid Range: 0.0, 20000.0

Description: The minimum of the nighttime digital counts measured by WFC at 1 km resolution for the current day for that pixel.

125m_Pixel_Values_Min

Units: count

Format: Float_32

Valid Range: 0.0, 20000.0

Description: The minimum of the nighttime digital counts measured by WFC at 125 m resolution for the current day for that pixel.

Metadata Parameter Descriptions

Product_ID

An 80-byte character string containing the product name. For the WFC Level 1 data, this parameter is "WFC_L1_Assembler".

Date_Time_at_Granule_Start

A 27-byte character string that specifies the granule start date and time. The format is yyyy-mm-ddThh:mm:ss.ffffffZ.

Date_Time_at_Granule_End

A 27-byte character string that specifies the granule end date and time. The format is yyyy-mm-ddThh:mm:ss.ffffffZ.

Date_Time_of_Production

A 27-byte character string that specifies the granule production. The format is yyyy-mm-ddThh:mm:ss.ffffffZ.

Frame_Time

Reports the total amount of time, in milliseconds, for a frame of data.

Integration_Time

Reports the total amount of time, in milliseconds, the CCD is exposed to light during a single data acquisition.

Relevant External Documentation

Michael C. Pitts, Larry W. Thomason, Yongxiang Hu, and David M. Winker "An assessment of the on-orbit performance of the CALIPSO wide field camera", Proc. SPIE 6745, Remote Sensing of Clouds and the Atmosphere XII, 67450K (25 October 2007); <https://doi.org/10.1117/12.737377>.

Data Release Information

Table 1: dates, versions, and production strategy for all CALIPSO WFC level 1 data releases

| WFC Lidar Level 1 | | | |
|-------------------|---------|-------------------------------------|---------------------|
| Release Date | Version | Data Date Range | Production Strategy |
| October 2025 | 4.00 | June 13, 2006 to April 10, 2020 | Standard |
| December 2011 | 3.02 | November 11, 2011 to April 10, 2020 | Validated Stage 1 |
| May 2010 | 3.01 | June 13, 2006 to October 29, 2009 | Validated Stage 1 |
| December 2006 | 1.10 | June 13, 2006 to September 21, 2010 | Provisional |

Data Quality Information

Data Quality Statement for the release of the CALIPSO WFC Level 1 Product Version 4.00

For the final release of the WFC data product two major changes were made.

Inclusion of Assembler and Calibration Files

Two intermediate products are generated as part of the WFC Level 1 processing that were previously not released, but for the final release will be. The calibration data product contains geolocated nighttime digital count data. The calibration data is collected over a 25-second segment on the dark side of every orbit. The assembler data products contain geolocated nighttime daily digital count and daily statistical data which comes from the calibration product. The assembler algorithm takes the calibration data and calculates the statistics for each pixel (mean, standard deviation, maximum, and minimum).

Update Format of CALIPSO HDF Files

The V4.0 WFC data products are distributed as Hierarchical Data Format Version 4 (HDF4) files, consistent with the EOS requirement in effect when CALIPSO launched in 2006. Since launch, there have been substantial technological advances in data discoverability and access resources. To make this data more readily accessible to the scientific community beyond the life of the mission and take advantage of newer data access capabilities, several modifications were made to the look and format of the WFC HDF files. These include:

- Update all units to conform to [NetCDF Climate and Forecast \(CF\)](#) metadata conventions.
- Verify all dimensions are named, to allow HDF to NCDF conversions using commercial off the shelf (COTS) tools that currently exist.
- Create/expand attributes and comments for all SDSs to make the data products more self-documenting.

Data Quality Statement for the release of the CALIPSO WFC Level 1 Product Version 3.02

The CALIPSO Team is releasing Version 3.02 which represents a transition of the Lidar, IIR, and WFC processing and browse code to a new cluster computing system. No algorithm changes were introduced, and very minor changes were observed between V 3.01 and V 3.02 as a result of the compiler and computer architecture differences. Version 3.02 is being released in a forward processing mode beginning November 1, 2011.

Data Quality Statement for the release of the CALIPSO WFC Level 1 Product Version 3.01

WFC Level 1B Scans Version 3.01 includes new metadata parameters and corrections to several minor software bugs. Specifically, the Orbit Number and Path Number metadata parameters are now included to facilitate improved sub-setting capabilities.

Data Quality Statement for the release of the CALIPSO WFC Level 1 Product Version 1.10

The WFC is currently fully functional and operating nominally. To date, the WFC data quality assessments have been focused on two primary areas: geolocation and radiometric accuracy. Post-launch checks of the WFC geolocation identified both along-track and cross-track biases in the reported WFC pixel locations. These systematic offsets were on the order of several 100 meters and were attributed to a small, uncharacterized misalignment of the WFC relative to the spacecraft platform. Geolocation corrections have been implemented in the Level 1 ground processing to eliminate these biases. WFC geolocation accuracy for the V1.10 data release is estimated to be better than 50 m. The initial assessment of the WFC radiometric performance was based on comparisons with the well-calibrated Aqua MODIS Channel 1 data. Preliminary comparisons indicated that the WFC radiometric measurements were biased high relative to MODIS by about 10%. Further investigation revealed that an offset in

the reported WFC exposure time was the likely cause of this bias. A review of pre-launch ground test data and results from diagnostic experiments performed on-orbit confirmed that the true WFC exposure time is about 0.4 ms longer than reported. Accounting for this exposure time offset results in about a 9% reduction in the magnitude of the WFC radiance values. This correction has been implemented in the Level 1 processing for the V1.10 data release. The WFC V1.10 radiometric measurements now exhibit excellent agreement with MODIS, with differences typically less than 2% over bright targets.